

TECHNICAL DATA KÄHRS LUXURY TILES



Dry back Stone 457 x 457 x 2.5 x 0.7 mm
5.01 m²/box



Dry back Stone 305 x 609 x 2.5 x 0.7 mm
2.58 m²/box



Dry back Herringbone 102 x 457 x 2.5 x 0.7 mm
2.78 m²/box



Dry back Wood 152.4 x 914.4 x 2.5 x 0.7 mm
3.34 m²/box






Dry back Wood 228.6 x 1219.2 x 2.5 x 0.7 mm
3.9 m²/box

PRODUCT











Dry back	EN ISO 10582	Luxury Vinyl Tile
Application	EN ISO 10874	23/34/43



SPECIFICATION

Thickness		EN ISO 24337	2.5 mm
Weight		EN ISO 24342	4.2 kg/m ²
Wear layer		EN ISO 24346	0.7 mm

PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, FloorScore, A+
Fire resistance	 EN 13501-1	Bfl-s1
Residual indentation	 EN 433	≤ 0.05 mm
Dimensional stability	 EN 434	< 0.1 %
Colour fastness	 EN ISO 105-B02	≥ 6
Slip resistance	 EN 13893 DIN 51130	DS (> 0.3) R10
Electrical propensity	 EN 1815	< 2 kV (antistatic)
Wear resistance	 EN 660-2	< 2.0 mm ³ (Class T)
Chemical resistance	 EN ISO 26987	Pass with good results
Effect of castor chair	 EN 425	Suitable
Underfloor heating		Ok (max +27 °C)
Bacterial growth		Does not act as substrate

Cleaning and maintenance instructions, see: www.kahrs.com

