## 2000 PUR

Attractive, high performance, heavy duty homogeneous sheet and tile floorcovering with a polyurethane reinforcement for low cost, lifetime polish free maintenance.

Featuring a directional duotone marbleised decoration, with marbleised highlight tones, 2000 PUR is available in a broad palette of vibrant shades. Demonstrating outstanding durability and abrasion resistance, 2000 PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.



Responsible Sourcing	BES 6001	Excellent	
VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test Floorscore Finnish MI Classification* Swedish B.P.D (FLEC test)* GBCA/NZGBC Green Star IEQ-VOC	Eurofins certified product Pass Certified Pass Best Class Compliant	*2.0mr
Maritime Usage	American Bureau of Shipping* US Coast Guard Approved* Marine Equipment Directive 2014/90/EU* SOLAS 74*	Conforms Conforms Conforms Conforms	*2.0mr
Castor Chair (continuous use)	EN 425/ISO 4918	Suitable	
Electrical behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'	
Indentation Residual	ASTM F970 (Modified)	Static load 750psi	
Slip Resistance	EN 13893 AS/NZS 4586	Class DS R9	
Binder Content	EN ISO 10581	Туре II	
Abrasion Resistance	EN 660-2	Group M	
Reaction to Fire	ASTM E662* ASTM E648*	<450 Class 1	*2.0m
Use Area	EN 685/ISO 10874	Class Bfl-S1	
General Performance	EN 649/EN ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Conforms	
Total Weight	EN 430/ISO 23997	2.0mm: 3550g/m <sup>2</sup> 2.5mm: 4552g/m <sup>2</sup>	
Tile Size	EN 427/ISO 24342	2.0mm: 300mm x 300mm = 4.5m <sup>2</sup> 2.0mm: 608mm x 608mm = 5.17m <sup>2</sup> 2.5mm: 300mm x 300mm = 3.6m <sup>2</sup>	
Roll Size	EN 426/ISO 24341	2.0mm: 2m x 20m = 40m <sup>2</sup> 2.5mm: 2m x 15m = 30m <sup>2</sup>	
Gauge	EN 428/ISO 24346	2.0mm 2.5mm	

Environmentally Preferable Flooring - Polyflor 2000 PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflor 2000 PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

PUR - Polyflor 2000 PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

SZ .

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.** The data presented is correct at the time of printing. For latest information, please visit our website **polyflor.com**.

Decoration and shade may vary slightly from the samples shown.





UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913 Sample Requests: +44 (0)161 767 2551 | email: info@polyflor.com | www.polyflor.com



FLOORING

James Halitead"