



## ASH AALBORG

This single-strip ash floor from the Sand Collection features a soft white matt lacquer finish, which eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
<b>Article Number</b>	151N8MAK1WKW220	<b>Wood Species</b>	Ash	<b>Moisture content</b>	EN13183	7%±2%
<b>Surface treatment</b>	Matt lacquer	<b>Board</b>	1-strip	<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Design features</b>	Microbevelled 4-sided	<b>Grading</b>	Calm (City)	<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Dimensions</b>	2266 x 187 x 15 mm	<b>Range</b>	Kährs Original	<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Weight per Package</b>	21 kg	<b>Collection</b>	Sand Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Area per Package</b>	2.54 m²	<b>Resandable</b>	2-3 times	<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Area Per Board</b>	0.423 m²	<b>Natural/Stained</b>	Stained	<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>DETAIL DESCRIPTION</b>	Even light colour with minor variations. Small sized knots in limited numbers allowed.		<b>Brinell Value</b>	4,0	<b>Thermal Resistance R-Value</b>	.11 (m2K/W)
<b>COLOUR CHANGE</b>	Stained product - noticable color change over time.		<b>Joint</b>	Woodloc® 5S	<b>Biological Durability</b>	EN350-2 Class 1
		<b>Floor heating</b>	Yes	<b>CARB2</b>		Compliant
		<b>Warranty</b>	30 years			
		<b>Wear-layer material</b>	Hardwood			
		<b>Wear-layer thickness</b>	3,5 mm			
		<b>Core material</b>	Pine/Spruce lamella			
		<b>Thickness</b>	15 mm			
		<b>Installation method</b>	Floating, glue-down			
		<b>Surface Colour</b>	White			

### CERTIFICATES

