

ASH BLACK COPPER

This striking, black-stained single-strip ash floor from the Shine Collection features copper metallic highlights in the pores for a dramatic effect. Four-sided microbevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The high-gloss lacquer finish adds lustre, giving the floor a polished appearance while protecting the wood from daily wear.

PRODUCT DESCRIPTION		
Article Number	151N8AAKC8KW240	
Surface treatment	High gloss lacquer	
Design features	Mcrobevelled 4-sided	
Dimensions	2420 x 187 x 15 mm	
Weight per Package	22 kg	
Area per Package	2.72 m ²	
Area Per Board	0.453 m ²	

DETAIL DESCRIPTION

PRODUCT DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.

COLOUR CHANGE

Stained product - noticable color change over time.

FACTS		
Wood Species	Ash	
Board	1-strip	
Grading	Calm (City)	
Range	Kährs Supreme	
Collection	Shine Collection	
Resandable	2-4 times	
Natural/Stained	Stained	
Brinell Value	4,0	
Joint	Woodloc® 5S	
Roor heating	Yes	
	30 years	
Warranty	30 years	
Warranty Wear-layer material	30 years Hardwood	
-	Hardwood	
Wear-layer material	Hardwood	
Wear-layer material Wear-layer thickness	Hardwood 3, 5 mm	
Wear-layer material Wear-layer thickness Core material	Hardwood 3, 5 mm Pine/Spruce lamella	
Wear-layer material Wear-layer thickness Core material Backside material	Hardwood 3, 5 mm Pine/Spruce lamella Veneer	
Wear-layer material Wear-layer thickness Core material Backside material Thickness	Hardwood 3, 5 mm Pine/Spruce lamella Veneer 15 mm	

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATES

