



## ASH FLOW

The white structure and semi-transparent stain on this single-strip ash floor from the Lux Collection balances the light and dark contrasts in the wood, allowing the warm ash tones to softly filter through. Four-sided micro-bevelling at the edging ensures a classic full plank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AAKG4KW240	Wood Species	Ash	Moisture content	EN13183	7%±2%
Surface treatment	Ultra matt lacquer	Board	1-strip	Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Design features	Microbevelled 4-sided, brushed	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Lux Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m <sup>2</sup>	Resandable	2-3 times	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Area Per Board	0.453 m <sup>2</sup>	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
		Brinell Value	4, 0	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969045131			
		Surface Colour	White			

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time

### CERTIFICATES

