



## ASH SANDVIG

This single-strip ash floor from the Sand Collection features the natural, warm core of the timber creating a pleasant contrast with the powder light hues. The naturally occurring knots and colour variations in the grain are prominent give this floor a unique expression. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151L87AK0VKV240	Wood Species	Ash	Moisture content	EN13183	7%±2%
Surface treatment	Matt lacquer	Board	1-strip	Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Dimensions	2420 x 187 x 15 mm	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	22 kg	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Area per Package	2.72 m <sup>2</sup>	Collection	Sand Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0.453 m <sup>2</sup>	Resandable	2-3 times	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
<b>DETAIL DESCRIPTION</b>		Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.		Brinell Value	4,0	Thermal Resistance R-Value		.11 (m <sup>2</sup> K/W)
<b>COLOUR CHANGE</b>		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Stained product - noticable color change over time.		Floor heating	Yes	<b>CARB2</b>		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3,5 mm			
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969028202			
		Surface Colour	White A0V			

### CERTIFICATES

