

BEECH OPAQUE

The white, semi-transparent stain on this single-strip beech floor from the Shine Collection enhances the alabaster hue of the timber. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The high-gloss lacquer finish adds lustre, giving the floor a polished appearance while protecting the wood from daily wear.

PRODUCT DESCRIPTION		
Article Number	151N8MBKW8KW240	
Surface treatment	High gloss lacquer	
Design features	Microbevelled 4-sided	
Dimensions	2420 x 187 x 15 mm	
Weight per Package	22 kg	
Area per Package	2.72 m ²	
Area Per Board	0.453 m²	

DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots will vary in size and numbers.

COLOUR CHANGE

Stained product - noticable color change over time.

FACTS		
Wood Species	Beech	
Board	1-strip	
Grading	Calm (City)	
Range	Kährs Supreme	
Collection	Shine Collection	
Resandable	2-4 times	
Natural/Stained	Stained	
Brinell Value	3,8	
Joint	Woodloc® 5S	
Roor heating	No	
Hoor heating Warranty	No 30 years	
Warranty	30 years Hardwood	
Warranty Wear-layer material	30 years Hardwood	
Warranty Wear-layer material Wear-layer thickness	30 years Hardwood 3, 5 mm	
Warranty Wear-layer material Wear-layer thickness Core material	30 years Hardwood 3, 5 mm Pine/Spruce lamella	
Warranty Wear-layer material Wear-layer thickness Core material Backside material	30 years Hardwood 3, 5 mm Pine/Spruce lamella Veneer	
Warranty Wear-layer material Wear-layer thickness Core material Backside material Thickness	30 years Hardwood 3, 5 mm Pine/Spruce lamella Veneer 15 mm	

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATES

