

OAK ANZIANO

This oiled, 3-strip floor from the Da Capo collection features an intentional colour variation in the boards, ranging from powder white to dusty brown to create a dramatic and weathered look. Water stains in combination with the knots and cracks in the boards result in a beautifully aged expression. Each plank is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

	PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPE	
	Article Number	153XCDEKWMKW190	Wood Species	Oak	Moisture content	
	Surface treatment	Oil	Board	3-strip	Minimun Mean Der	
	Design features	Brushed, saw marks	Grading	Expressive	Reaction To Fire	
	Dimensions	1900 x 190 x 15 mm	Range	Kährs Supreme	Formaldehyde Emi	
	Weight per Package	19 kg	Collection	Da Capo Collection	Content PCP	
	Area per Package	2.17 m²	Resandable	2-4 times	Breaking Strength	
	Area Per Board	0.361 m ²	Natural/Stained	Stained	Thermal Conductiv	
			Brinell Value	3,7	Thermal Resistance	
	DETAIL DESCRIPTION		Joint	Woodloc®	Biological Durabilit	

All naturally occuring wood colour variations						
allowed, from light to dark brown. Sapwood						
may occur. The product includes very large						
sound and black knots and cracks. Knots and						
cracks will be present in all sizes and						
numbers.						

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS		TECHNICAL PROPERTIES			
Wood Species	Oak	Moisture content	EN13183	7%±2%	
Board	3-strip	Minimun Mean Density kg/m³		>500 kg/m³	
Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1	
Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1	
Collection	Da Capo Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n	
Resandable	2-4 times	Breaking Strength Wmm²	EN1533	NPD	
Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK	
Brinell Value	3,7	Thermal Resistance R-Value		.11 (m2K/W)	
Joint	Woodloc®	Biological Durability	EN350-2	Class 1	
Roor heating	Yes	CARB2		Compliant	
Warranty	30 years				
Wear-layer material	Hardwood				
Wear-layer thickness	3, 5 mm				
Core material	Pine/Spruce lamella				
Backside material	Veneer				
Thickness	15 mm				
Installation method	Glue-down, floating				

CERTIFICATES

