

## **OAK ATTEBO**

The cigarillo brown nuances featured in this 3-strip oak floor from the Götaland Collection are enhanced by flashes of rich charcoal and burnt embers, resulting in a moderately rich colour variation and a refined expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N66EK04KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
		Board	3-strip	Minimun Mean Density kg/m³		>500 kg/m³
Surface treatment	Oil	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Bevelled 4-sided, handscraped, brushed, saw marks	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
		Collection	Götaland Collection	Content PCP	CEN/TR14823	≤5 x 10-6n
Dimensions	2419 x 196 x 15 mm	Resandable	2-3 times	Breaking Strength Wmm²	EN1533	NPD
Weight per Package	22.4 kg	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Area per Package	2.84 m <sup>2</sup>	Brinell Value	3,7	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Area Per Board	0.474 m²	Roor heating	Yes	CARB2		Compliant
		Warranty	30 years			
DETAIL DESCRIPTION		Wear-layer material	Hardwood			
Contains knots and all natural colour variations.  COLOUR CHANGE  The colour matures over time		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969042789			
		Surface Colour	Dark brown			

## CERTIFICATES

