



OAK BACKKA

The deep amber hue of this 3-strip oak floor from the Götaland Collection is subtly enhanced by charcoal knots and cracks, creating a classic yet luxurious expression. Occasional saw marks accentuate the floor's natural appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N66EK02KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	3-strip	Minimum Mean Density kg/m³		>500 kg/m³
Design features	Bevelled 4-sided, handscraped, brushed, saw marks	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2419 x 196 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22.4 kg	Collection	Götaland Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.84 m²	Resandable	2-3 times	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.474 m²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
COLOUR CHANGE		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
Contains knots and all natural colour variations.		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969042796			
		Surface Colour	Light Brown			

CERTIFICATES

