



## OAK BODA

The warm, golden tones in this 3-strip oak floor from the Götländ Collection are punctuated by naturally occurring knots and cracks, resulting in a timeless and classic expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
<b>Article Number</b>	153N66EK01KW240	<b>Wood Species</b>	Oak	<b>Moisture content</b>	EN13183	7%±2%
<b>Surface treatment</b>	Oil	<b>Board</b>	3-strip	<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Design features</b>	Bevelled 4-sided, handscraped, brushed, saw marks	<b>Grading</b>	Dynamic	<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Dimensions</b>	2419 x 196 x 15 mm	<b>Range</b>	Kährs Original	<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Weight per Package</b>	22.4 kg	<b>Collection</b>	Götländ Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Area per Package</b>	2.84 m²	<b>Resandable</b>	2-3 times	<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Area Per Board</b>	0.474 m²	<b>Natural/Stained</b>	Natural	<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>DETAIL DESCRIPTION</b>	Contains knots and all natural colour variations.	<b>Brinell Value</b>	3, 7	<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>COLOUR CHANGE</b>	The colour matures over time	<b>Joint</b>	Woodloc® 5S	<b>Biological Durability</b>	EN350-2	Class 1
		<b>Floor heating</b>	Yes	<b>CARB2</b>		Compliant
		<b>Warranty</b>	30 years			
		<b>Wear-layer material</b>	Hardwood			
		<b>Wear-layer thickness</b>	3, 5 mm			
		<b>Core material</b>	Pine/Spruce/Alder			
		<b>Backside material</b>	Spruce			
		<b>Thickness</b>	15 mm			
		<b>Installation method</b>	Floating, glue-down			
		<b>EAN Code</b>	7393969042772			

### CERTIFICATES

