



OAK CADENCE

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES	
Article Number	13103AEK1PKW185	Wood Species	Oak	TestMoistureContent	7%±2%
EANCode	7393969107358	Board	1-strip	TestMinimunMeanDensity	>500 kg/m ³
Surface treatment	Matt lacquer	Grading	Calm	TestReactionToFire	Dfl-s1
Design features	Microbevelled 4-sided, Brushed	Range	Kährs Avanti	TestFormaldehydeEmission	E1
		Collection	Canvas Collection	TestContentPCP	≤ 5 x 10-6n
Dimensions	1860 x 127 x 13 mm	Resandable	2-3 times	TestBreakingStrength	NPD
Weight per Package x	12.69 kg	Natural/Stained	Stained	TestThermalConductivity	0,08 W/mK
AreaPerPalletM2	104.1	Brinell Value	3,7	TestThermalResistanceRValue	e .15 (m2K/W)
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5G	TestBiologDurability	Class 1
		Floor heating	Yes	TestCarb2	Compliant
COLOUR CHANGE		Warranty	25 years		
Stained product - noticeable color change over time.		Wear-layer material	Hardwood		
		Wear-layer thickness	3 mm		
		Core material	Pine/Spruce lamella		
		Thickness	13 mm		
		Surface Colour	Dark brown		



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.