

OAK CAMINO

The warm ginger tones in this single-strip oak floor from the Artisan Collection are enhanced by a natural oil finish, which highlights the charcoal knots and cracks. Each board is carefully brushed to bring out the character of the grain and emphasises the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

TECHNICAL PROPERTIES

Minimun Mean Density kg/m³

Formaldehyde Emission

Breaking Strength N/mm²

Thermal Resistance R-Value

Thermal Conductivity

Biological Durability

CARB2

EN13183

EN13501-1

EN717-1

EN1533

EN12664

EN350-2

7%±2%

Dfl-s1

F1

NPD

0,14 W/mK

.11 (m2K/W)

Class 1

Compliant

CEN/TR14823 ≤ 5 x 10-6n

>500 kg/m³

Moisture content

Reaction To Fire

Content PCP

| PRODUCT DESCRIPTION | | |
|-----------------------|--|--|
| Article Number | 151XDDEKFZKW190 | |
| Surface treatment | Oil | |
| Design features | Bevelled 4-sided, brushed, handscraped | |
| Dimensions | 1900 x 190 x 15 mm | |
| Weight per Package | 17 kg | |
| Area per Package | 2.17 m ² | |
| Area Per Board | 0.361 m² | |

DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Some muting of colour variation to medium,

| Wood Species | Oak |
|----------------------|---------------------|
| Board | 1-strip |
| Grading | Dynamic |
| Range | Kährs Original |
| Collection | Artisan Collection |
| Resandable | 2-3 times |
| Natural/Stained | Natural |
| Joint | Woodloc® |
| Roor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3, 5 mm |
| Core material | Pine/Spruce lamella |
| Thickness | 15 mm |
| Installation method | Floating, glue-down |
| EAN Code | 7393969031431 |

Rustic natur

FACTS

Surface Colour

straw brown.

CERTIFICATES

