



OAK CHEVRON LIGHT BROWN

The lightly smoked finish this on this ready-to-install, patterned oak board from the Chevron Collection enriches its warm toffee hue and brings a modern expression to its traditional look. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Partial handcrafting gives each board its unique appearance, while micro-bevelling enhances the iconic geometric design.

Right Version

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151XADEKWKW18R	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	Pattern	Minimum Mean Density kg/m³		>500 kg/m³
Design features	Bevelled 4-sided, brushed, light smoked	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1848 x 305 x 15 mm	Range	Kährs ID	Formaldehyde Emission	EN717-1	E1
Weight per Package	20.01 kg	Collection	Chevron Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Status in Movex	20	Resandable	2-3 times	Breaking Strength N/mm²	EN1533	NPD
Area per Package	2.04 m²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Area Per Board	0.51 m²	Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
DETAIL DESCRIPTION	Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers..	Joint	Tongue & Groove	Biological Durability	EN350-2	Class 1
COLOUR CHANGE	Stained product - noticable color change over time.	Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Poplar			
		Backside material	Oak			
		Thickness	15 mm			
		Installation method	Glue-down			
		EAN Code	7393969041928			
		Surface Colour	Mature oak			
CERTIFICATES						

