



## OAK DIM

This 2-strip, stained oak floor from the Lumen Collection features warm, earth tones pooled with stone grey hues. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	152N7BEKD4KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Ultra matt lacquer	Board	2-strip	Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Design features	Brushed	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2423 x 200 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Collection	Lumen Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.91 m <sup>2</sup>	Resandable	2-3 times	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Area Per Board	0.485 m <sup>2</sup>	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
<b>DETAIL DESCRIPTION</b>		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Naturally occurring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers.		Floor heating	Yes	<b>CARB2</b>		Compliant
		Warranty	30 years			
<b>COLOUR CHANGE</b>		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
Stained product - noticeable color change over time		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969044806			
		Surface Colour	Earth Grey			

### CERTIFICATES

