



## OAK DOME

The honey hues found in this single-strip oak floor from the Habitat Collection enhance the grain with a warm colour palette. The floor comes with long planks, which add depth to its clean expression. Four-sided bevelling at the edges ensures a classic full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DESCRIPTION  |                                | FACTS                |                     | TECHNICAL PROPERTIES                   |             |                          |
|--|--------------------------------|----------------------|---------------------|--|-------------|--------------------------|
| Article Number   | 37101AEKC1KW180                | Wood Species         | Oak                 | Moisture content                       | EN13183     | 7%±2%                    |
| Surface treatment  | Matt lacquer                   | Board                | 1-strip             | Minimum Mean Density kg/m <sup>3</sup> |             | >800 kg/m <sup>3</sup>   |
| Design features  | Brushed, microbevelled 4-sided | Grading              | Calm (City)         | Reaction To Fire                       | EN13501-1   | Cfl-s1                   |
| Dimensions   | 1810 x 150 x 7 mm              | Range                | Kährs Linnea        | Formaldehyde Emission                  | EN717-1     | E1                       |
| Weight per Package   | 20 kg                          | Collection           | Habitat Collection  | Content PCP                            | CEN/TR14823 | ≤ 5 x 10 <sup>-6</sup> n |
| Area per Package   | 3.26 m <sup>2</sup>            | Resandable           | Not resandable      | Breaking Strength N/mm <sup>2</sup>    | EN1533      | NPD                      |
| Area Per Board   | 0.272 m <sup>2</sup>           | Natural/Stained      | Stained             | Thermal Conductivity                   | EN12664     | 0,22 W/mK                |
| DETAIL DESCRIPTION   |                                | Brinell Value        | 5 - 6               | Thermal Resistance R-Value             |             | .031 (m2K/W)             |
|  |                                | Joint                | Woodloc®            | Biological Durability                  | EN350-2     | Class 1                  |
| COLOUR CHANGE  |                                | Floor heating        | Yes                 | CARB2                                  |             | Compliant                |
|  |                                | Warranty             | 12 years            |  |             |                          |
| Even colour with minor variations. Small sized knots in limited numbers allowed. |                                | Wear-layer material  | Hardwood            |  |             |                          |
|  |                                | Wear-layer thickness | 0,6 mm              |  |             |                          |
|  |                                | Core material        | HDF                 |  |             |                          |
|  |                                | Thickness            | 7 mm                |  |             |                          |
|  |                                | Installation method  | Floating, glue-down |  |             |                          |
|  |                                | EAN Code             | 7393969106689       |  |             |                          |
|  |                                | Surface Colour       | White C1            |  |             |                          |

### CERTIFICATES

