

## **OAK ECLIPSE**

The mineral grey notes in this 3-strip oak floor from the Lumen Collection are awash with stoney earth tones, eloquently complemented by the ultra-matt lacquer finish. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N3BEKE4KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Ultra matt lacquer	Board	3-strip	Minimun Mean Density kg/m³		>500 kg/m <sup>3</sup>
Design features	Brushed	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2423 x 200 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Collection	Lumen Collection	Content PCP	CEN/TR14823	≤5 x 10-6n
Area per Package	2.91 m²	Resandable	2-3 times	Breaking Strength Wmm²	EN1533	NPD
Area Per Board	0.485 m <sup>2</sup>	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Even colour with minor variations. Small sized knots in limited numbers allowed.		Roor heating	Yes	CARB2		Compliant
		Warranty	30 years			
COLOUR CHANGE		Wear-layer material	Hardwood			
Stained product - noticeable color change over time		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce/Ader			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969044288			
		Surface Colour	Grey			

## CERTIFICATES

