



Kährs
QUALITY IN WOOD SINCE 1857

OAK FUMOIR

The light-smoked finish of this single-strip oak floor from the Shine Collection enhances the colour variation in the timber, which ranges from a fair brunette to a warm stone hue. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The high-gloss lacquer finish adds lustre, giving the floor a polished appearance while protecting the wood from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N3REKD8KW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	High gloss lacquer	Board	1-strip	Minimum Mean Density kg/m³		>500 kg/m ³
Design features	Microbevelled 4-sided, light smoked	Grading	Calm (City)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1800 x 130 x 15 mm	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1
Weight per Package	11 kg	Collection	Shine Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	1.40 m ²	Resandable	2-4 times	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.233 m ²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION	Even colour with minor variations. Small sized knots in limited numbers allowed.	Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
COLOUR CHANGE	Stained product - noticeable color change over time.	Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Backside material	Veneer			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969035484			
		Surface Colour	Grey D8			

CERTIFICATES

