

OAK GUSTAF

The muted white stain on this single-strip oak floor from the Founders Collection creates a serene background to the naturally occurring knots and cracks, resulting in a beautifully rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N7BEKFVKW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
		Board	1-strip	Minimun Mean Density kg/m ³		>500 kg/m ³
Surface treatment	Oil	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Bevelled 4-sided, handscraped, brushed	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
		Collection	Founders Collection	Content PCP	CEN/TR14823	≤5 x 10-6n
Dimensions	2420 x 187 x 15 mm	Resandable	2-3 times	Breaking Strength Nmm ²	EN1533	NPD
Weight per Package	22 kg	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Area per Package	2.72 m ²	Brinell Value	3,7	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Area Per Board	0.453 m²	Roor heating	Yes	CARB2		Compliant
		Warranty	30 years			
DETAIL DESCRIPTION		Wear-layer material	Hardwood			
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
namboro.		EAN Code	7393969036061			
COLOUR CHANGE		Surface Colour	White IFV			

Stained product - noticable color change over time.

CERTIFICATES