



OAK HANDBÖRD

The cloudy stain on this single-strip oak floor from the Småland Collection allows the lightly smoked nuances in the wood to seep through, resulting in a very rustic expression. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151NDSEK06KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m³		>500 kg/m ³
Design features	Bevelled 4-sided, brushed, light smoked, handscraped, saw marks	Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Småland Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m ²	Resandable	2-4 times	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.453 m ²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m ² K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Backside material	Veneer			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969039079			
		Surface Colour	Grey			

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

CERTIFICATES

