

OAK HORIZON

This single-strip oak floor from the Lux Collection features a misty white transparent stain, which allows distinctive gradations in the wood to come through. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DESCRIPTION | | FACTS | | TECHNICAL PROPERTIES | | |
|---|-----------------------------------|----------------------|---------------------|--|-------------|------------------------|
| Article Number | 151N8AEKC4KW240 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| Surface treatment | Ultra matt lacquer | Board | 1-strip | Minimun Mean Density kg/m ³ | | >500 kg/m ³ |
| | | Grading | Lively (Country) | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Design features | Microbevelled 4-sided, brushed | Range | Kährs Original | Formaldehyde Emission | EN717-1 | E1 |
| Dimensions | 2420 x 187 x 15 mm | Collection | Lux Collection | Content PCP | CEN/TR14823 | ≤5 x 10-6n |
| Weight per Package | 22 kg | Resandable | 2-3 times | Breaking Strength Nmm ² | EN1533 | NPD |
| | | Natural/Stained | Stained | Thermal Conductivity | EN12664 | 0,14 W/mK |
| Area per Package | 2.72 m ² | Brinell Value | 3,7 | Thermal Resistance R-Value | | .11 (m2K/W) |
| Area Per Board | 0.453 m ² | Joint | Woodloc® 5S | Biological Durability | EN350-2 | Class 1 |
| | | Roor heating | Yes | CARB2 | | Compliant |
| DETAIL DESCRIPTION | | Warranty | 30 years | | | |
| Al naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers. | | Wear-layer material | Hardwood | | | |
| | | Wear-layer thickness | 3, 5 mm | | | |
| | | Core material | Pine/Spruce/Ader | | | |
| | | Backside material | Spruce | | | |
| | | Thickness | 15 mm | | | |
| COLOUR CHANGE | | Installation method | Floating, glue-down | | | |
| Stained product - noticable color change over time | | EAN Code | 7393969044196 | | | |
| | | Surface Colour | White | | | |

CERTIFICATES