



## OAK KILESAND

The natural grain of the wood in this 3-strip oak floor from the Götaland Collection is enhanced by pastel grey and white notes in the knots and cracks, resulting in an organic expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
<b>Article Number</b>	153N66EK05KW240	<b>Wood Species</b>	Oak	<b>Moisture content</b>	EN13183	7%±2%
<b>Surface treatment</b>	Oil	<b>Board</b>	3-strip	<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Design features</b>	Bevelled 4-sided, handscraped, brushed, saw marks	<b>Grading</b>	Dynamic	<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Dimensions</b>	2419 x 196 x 15 mm	<b>Range</b>	Kährs Original	<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Weight per Package</b>	22.4 kg	<b>Collection</b>	Götaland Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Area per Package</b>	2.84 m²	<b>Resandable</b>	2-3 times	<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Area Per Board</b>	0.474 m²	<b>Natural/Stained</b>	Stained	<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
		<b>Brinell Value</b>	3, 7	<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
		<b>Joint</b>	Woodloc® 5S	<b>Biological Durability</b>	EN350-2	Class 1
		<b>Floor heating</b>	Yes	<b>CARB2</b>		Compliant
		<b>Warranty</b>	30 years			
		<b>Wear-layer material</b>	Hardwood			
		<b>Wear-layer thickness</b>	3, 5 mm			
		<b>Core material</b>	Pine/Spruce/Alder			
		<b>Backside material</b>	Spruce			
		<b>Thickness</b>	15 mm			
		<b>Installation method</b>	Floating, glue-down			
		<b>EAN Code</b>	7393969042819			
		<b>Surface Colour</b>	White			
<b>DETAIL DESCRIPTION</b>						
Contains knots and all natural colour variations.						
<b>COLOUR CHANGE</b>						
The colour matures over time						

### CERTIFICATES

