

OAK KINDA

The earthen grey stain on this single-strip oak floor from the Småland Collection allows the warmer tones in the base to come through, resulting in a very rustic expression with a delicately balanced colour variation. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PF
Article	151NDSEK02KW240	Wood Species	Oak	Moisture conte
Number		Board	1-strip	Minimun Mean
Surface treatment	Oil	Grading	Expressive	Reaction To Fi
Design	, i ,	Range	Kährs Supreme	Formaldehyde
features		Collection	Småland Collection	Content PCP
Dimensions	2420 x 187 x 15 mm	Resandable	2-4 times	Breaking Stre
Weight per Package	22 kg	Natural/Stained	Stained	Thermal Cond
Status in	20	Brinell Value	3,7	Thermal Resis
Movex	20	Joint	Woodloc® 5S	Biological Dura
Area per Package	2.72 m ²	Roor heating	Yes	CARE2
		Warranty	30 years	
Area Per Board	0.453 m²	Wear-layer material	Hardwood	
		Wear-layer thickness	3, 5 mm	
DETAIL DESC	CRIPTION	Core material	Pine/Spruce lamella	
Al naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and		Thickness	15 mm	
		Installation method	Floating, glue-down	
		EAN Code	7393969039031	

Surface Colour

Earth Grey

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m ³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤5 x 10-6n
Breaking Strength Nmm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

COLOUR CHANGE

numbers.

The colour matures over time.

CERTIFICATES