



OAK MAGGIORE

The black-and-tan colour range in this single-strip floor from the Da Capo Collection results in an extremely rustic expression. The naturally occurring knots and cracks add to the quality of the surface, giving the floor a worn complexion reminiscent of reclaimed timber. Each board is carefully brushed to bring out the quality of the grain and highlight the natural properties of the wood. Two-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged appearance of the floor.

PRODUCT DESCRIPTION

| | |
|---------------------------|--|
| Article Number | 151XDDEKF0KW190 |
| Surface treatment | Oil |
| Design features | Handscraped, bevelled 2-sided, brushed |
| Dimensions | 1900 x 190 x 15 mm |
| Weight per Package | 19 kg |
| Area per Package | 2.17 m ² |
| Area Per Board | 0.361 m ² |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Board | 1-strip |
| Grading | Expressive |
| Range | Kährs Supreme |
| Collection | Da Capo Collection |
| Resandable | 2-4 times |
| Natural/Stained | Natural |
| Brinell Value | 3, 7 |
| Joint | Woodloc® |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3, 5 mm |
| Core material | Pine/Spruce lamella |
| Backside material | Veneer |
| Thickness | 15 mm |
| Installation method | Glue-down, floating |
| EAN Code | 7393969033459 |
| Surface Colour | Light Brown F0 |

TECHNICAL PROPERTIES

| | | |
|--|-------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .11 (m ² K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |

CERTIFICATES

