



OAK MENTON

This 2-strip oak floor from the Sand Collection features warm tones highlighted by a white pigmented matt lacquer for a contemporary expression with subtle contrasts in the planks. The light finish enhances the even grade of the boards, resulting in a soft and smooth appearance.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	152N3BEKB1KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Matt lacquer	Board	2-strip	Minimum Mean Density kg/m³		>500 kg/m³
Design features	Brushed	Grading	Variation (Town)	Reaction To Fire	EN13501-1	DI-s1
Dimensions	2423 x 200 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Collection	Sand Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.91 m²	Resandable	2-3 times	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.485 m²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Naturally occurring wood colour variations allowed, from light to dark brown. Will include sapwood. The product includes medium sound and black knots. Knots may vary in size and numbers.		Floor heating	Yes	CARB2		
		Warranty	30 years	Compliant		
COLOUR CHANGE		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
Stained product - noticeable color change over time		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969043946			
		Surface Colour	White			

CERTIFICATES

