

OAK NOUVEAU BRONZE

The bronze pigments found in this single-strip, white oak floor from the Classic Nouveau Collection beautifully accentuate the warm caramel undertones, resulting in an elegant expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DESCRIPTION | | FACTS | | TECHNICAL PROPERTIES | | |
|---|------------------------------|-------------------------|---------------------|--|-------------|-------------|
| Article Number | 151L8AEK1GKW240 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| Surface treatment | Matt lacquer | Board | 1-strip | Minimun Mean Density kg/m ³ | | >500 kg/m³ |
| Design features | Bevelled 4-sided, brushed | Grading | Lively (Country) | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | | Range | Kährs Original | Formaldehyde Emission | EN717-1 | E1 |
| Dimensions | 2420 x 187 x 15 mm | Collection | Classic Nouveau | Content PCP | CEN/TR14823 | ≤5 x 10-6n |
| Weight per Package | 22 kg | | Collection | Breaking Strength Nmm ² | EN1533 | NPD |
| Area per Package | 2.72 m ² | Resandable | 2-3 times | Thermal Conductivity | EN12664 | 0,14 W/mK |
| Area Per Board | 0.453 m² | Natural/Stained | Stained | Thermal Resistance R-Value | | .11 (m2K/W) |
| | | Brinell Value | 3,7 | Biological Durability | EN350-2 | Class 1 |
| DETAIL DESCRIPTION | | Joint | Woodloc® 5S | CARB2 | | Compliant |
| All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | | Roor heating | Yes | | | |
| | | Warranty | 30 years | | | |
| | | Wear-layer material | Hardwood | | | |
| COLOUR CHANGE | | Wear-layer thickness | 3, 5 mm | | | |
| Stained product - noticable color change over time. | | Core material | Pine/Spruce lamella | | | |
| | | Thickness | 15 mm | | | |
| | | Installation method | Glue-down, floating | | | |
| | | EAN Code | 7393969026055 | | | |
| | | | | | | |

Brown 1G

Surface Colour

CERTIFICATES