



OAK NOUVEAU GREIGE

The lightly smoked, grey-stain found on this single-strip oak floor from the Classic Nouveau Collection enhance the earth undertones and balance the natural contrasts in the wood. Knots and cracks lightly pepper the boards, adding subtle depth to the floor's elegant expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DESCRIPTION | | FACTS | | TECHNICAL PROPERTIES | | |
|--|--|----------------------|----------------------------|--|-------------|--------------------------|
| Article Number | 151N8AEKGGKW220 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| Surface treatment | Matt lacquer | Board | 1-strip | Minimum Mean Density kg/m ³ | | >500 kg/m ³ |
| Design features | Microbevelled 4-sided, brushed, light smoked | Grading | Lively (Country) | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Dimensions | 2266 x 187 x 15 mm | Range | Kährs Original | Formaldehyde Emission | EN717-1 | E1 |
| Weight per Package | 21 kg | Collection | Classic Nouveau Collection | Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Status in Movex | 20 | Resandable | 2-3 times | Breaking Strength N/mm ² | EN1533 | NPD |
| Area per Package | 2.54 m ² | Natural/Stained | Stained | Thermal Conductivity | EN12664 | 0,14 W/mK |
| Area Per Board | 0.423 m ² | Brinell Value | 3, 7 | Thermal Resistance R-Value | | .11 (m2K/W) |
| DETAIL DESCRIPTION | | Joint | Woodloc® 5S | Biological Durability | EN350-2 | Class 1 |
| All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | | Floor heating | Yes | CARB2 | | Compliant |
| COLOUR CHANGE | | Warranty | 30 years | | | |
| Stained product - noticeable color change over time. | | Wear-layer material | Hardwood | | | |
| CERTIFICATES | | Wear-layer thickness | 3, 5 mm | | | |
| | | Core material | Pine/Spruce lamella | | | |
| | | Thickness | 15 mm | | | |
| | | Installation method | Floating, glue-down | | | |
| | | EAN Code | 7393969041195 | | | |
| | | Surface Colour | Grey | | | |

