



OAK OUTPOST

The lightly smoked finish on this single-strip oak floor from the Habitat Collection enhances the grey and auburn hues in the timber. The naturally occurring knots and cracks highlight its rustic expression and add depth to the floor. Four-sided bevelling at the edges ensures a classic full plank look and feel. Each board is carefully brushed to bring out the character of the grain and the natural texture of the wood.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	37107AEKFMKW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m³		>800 kg/m ³
Design features	Microbevelled 4-sided, brushed, light smoked	Grading	Dynamic	Reaction To Fire	EN13501-1	Cfl-s1
Dimensions	1810 x 150 x 7 mm	Range	Kährs Linnea	Formaldehyde Emission	EN717-1	E1
Weight per Package	20 kg	Collection	Habitat Collection	Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Status in Movex	20	Resandable	Not resandable	Breaking Strength N/mm²	EN1533	NPD
Area per Package	3.26 m ²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,22 W/mK
Area Per Board	0.272 m ²	Brinell Value	5 - 6	Thermal Resistance R-Value		.031 (m ² K/W)
DETAIL DESCRIPTION	All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.	Joint	Woodloc®	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		Compliant
		Warranty	12 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	0,6 mm			
		Core material	HDF			
		Thickness	7 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969107099			
		Surface Colour	Warm grey			

COLOUR CHANGE

Stained product - noticeable color change over time.

CERTIFICATES

