



OAK PRATICA

The soft blonde tones in this single-strip oak floor from the Canvas Collection are enhanced by a chalky-grey stain resulting in a clean expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	13106AEK1UKW185	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969043175	Board	1-strip	content		
Surface treatment	Matt lacquer	Grading	Lively	Minimun Mean Density kg/m³ >500 kg/m³		
Design features	Microbevelled 4-sided,	Range	Kährs Avanti	Reaction To Fire	EN13501-1	Dfl-s1
	Brushed	_ Collection	Canvas Collection	Formaldehyde	EN717-1	E1
Dimensions	1860 x 127 x 13 mm	Resandable	2-3 times	Emission	2147171	
Weight per Package (kg)	12.687 kg	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package (m²)	1.652 m ²	Brinell Value	3,7	Breaking	EN1533	NPD
Area per pallet (m²)	104.076 m ²	Joint	Woodloc® 5G	Strength N/mm²		
Package info	Packages may contain start and stop boards.	Floor heating	Yes	Thermal	EN12664	0,08 W/mK
		Warranty	25 years	Conductivity		
DETAIL DESCRIPTION		Wear-layer material	Hardwood	Thermal Resistance R-Value		.15 (m2K/W)
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.		Wear-layer thickness	3 mm	Biological Durability	EN350-2	Class 1
		Core material	Pine/Spruce lamella	CARB2		Compliant
		Thickness	13 mm	CARB2		Compliant
will be present in all sizes	and nambers.	Installation method	Floating, Glue-down			

COLOUR CHANGE

 $\label{thm:continuous} \textbf{Stained product-noticeable color change over time.}$

CERTIFICATES









Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.