



OAK SAFARI

Intense brown nuances cover a honey-colour base, while well-defined knots and cracks give this single-strip oak floor from the the Rugged Collection its unmistakable character. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Light and dark contrasts in the wood are punctuated with occasional saw marks, giving the floor its restored appearance.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	101P8QEKFKKW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m ³		>800 kg/m ³
Design features	Microbevelled 4-sided, smoked, saw marks	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1830 x 125 x 10 mm	Range	Kährs Spirit	Formaldehyde Emission	EN717-1	E1
Weight per Package	16, 75 kg	Collection	Rugged Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	1.83 m ²	Resandable	1 time	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.228 m ²	Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Resistance R-Value		.07 (m2K/W)
COLOUR CHANGE		Joint	Woodloc®	Biological Durability	EN350-2	Class 1
Smoked product - little colour change.		Floor heating	Yes	CARB2		Compliant
		Warranty	20 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	1, 9 mm			
		Core material	HDF			
		Thickness	10 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969043809			
		Surface Colour	Brown FK			

CERTIFICATES

