



OAK SEVEDE

The subtle, amber stain on this single-strip oak floor from the Småland Collection allows the rich and warm tones in the wood to seep through, resulting in a lively expression and a naturally balanced contrast. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES	
Article Number	151NCSEK05KW240	Wood Species	Oak	Moisture content	EN13183 7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m³	>500 kg/m ³
Design features	Bevelled 4-sided, brushed, light smoked, handscraped	Grading	Dynamic	Reaction To Fire	EN13501-1 Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Supreme	Formaldehyde Emission	EN717-1 E1
Weight per Package	22 kg	Collection	Småland Collection	Content PCP	CEN/TR14823 ≤ 5 x 10-6n
Area per Package	2.72 m ²	Resandable	2-4 times	Breaking Strength N/mm²	EN1533 NPD
Area Per Board	0.453 m ²	Natural/Stained	Stained	Thermal Conductivity	EN12664 0,14 W/mK
		Brinell Value	3, 7	Thermal Resistance R-Value	.11 (m ² K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2 Class 1
		Floor heating	Yes	CARB2	Compliant
		Warranty	30 years		
		Wear-layer material	Hardwood		
		Wear-layer thickness	3, 5 mm		
		Core material	Pine/Spruce lamella		
		Backside material	Veneer		
		Thickness	15 mm		
		Installation method	Floating, glue-down		
		EAN Code	7393969039000		
		Surface Colour	Amber Brown		
DETAIL DESCRIPTION					
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.					
COLOUR CHANGE					
Stained product - noticeable color change over time.					

CERTIFICATES

