



OAK SHELL

The powder white finish with soft contrast on this 3-strip oak floor from the Harmony Collection allows the warmer nuances to come through. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N6BEKS1KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Matt lacquer	Board	3-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Design features	Brushed	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2423 x 200 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Collection	Harmony Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.91 m ²	Resandable	2-3 times	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.485 m ²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
COLOUR CHANGE		Floor heating	Yes	CARB2		
		Warranty	30 years	Compliant		
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969045124			
		Surface Colour	White			

CERTIFICATES

