

OAK SPARUTO

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Two-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

	PRODUCT DESCRIPTION		FACTS		
	Article Number	151XDDEKFRKW190	Wood Species	Oak	
			Board	1-strip	
	Surface treatment	Oil	Grading	Expre	
	Design features	Bevelled 2-sided, brushed, smoked, handscraped, wooden plugs	Range	Kährs	
			Collection	Da Ca	
	Dimensions		Resandable	2-4 tir	
	Weight per Package	19 kg	Natural/Stained	Natur	
			Brinell Value	3,7	
	Area per Package	2.17 m ²	Joint	Wood	
			Roor heating	Yes	
	Area Per Board	0.361 m ²	Warranty	30 ye	

DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Smoked product - noticable color change over time.

	FACTS		TECHNICAL PROPERTIES			
	Wood Species	Oak	Moisture content	EN13183	7%±2%	
	Board	1-strip	Minimun Mean Density kg/m³		>500 kg/m ³	
	Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1	
	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1	
	Collection	Da Capo Collection	Content PCP	CEN/TR14823	≤5 x 10-6n	
	Resandable	2-4 times	Breaking Strength N/mm²	EN1533	NPD	
	Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK	
	Brinell Value	3,7	Thermal Resistance R-Value		.11 (m2K/W)	
	Joint	Woodloc®	Biological Durability	EN350-2	Class 1	
	Roor heating	Yes	CARB2		Compliant	
	Warranty	30 years				
	Wear-layer material	Hardwood				
	Wear-layer thickness	3, 5 mm				
	Core material	Pine/Spruce lamella				
	Backside material	Veneer				
	Thickness	15 mm				
	Installation method	Floating, glue-down				
	EAN Code	7393969033473				
	Surface Colour	Brown FK				



CERTIFICATES