

## OAK STURE

The natural oil stain on this single-strip oak floor from the Founders Collection accentuates the lightly smoked finish, resulting in a subtle, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

| PRODUCT DESCRIPTION                                                                                                                                                                                                                             |                                                      | FACTS                |                     | TECHNICAL PROPERTIES                   |             |                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|----------------------|---------------------|----------------------------------------|-------------|------------------------|
| Article<br>Number                                                                                                                                                                                                                               | 151N7BEKFMKW240                                      | Wood Species         | Oak                 | Moisture content                       | EN13183     | 7%±2%                  |
|                                                                                                                                                                                                                                                 |                                                      | Board                | 1-strip             | Minimun Mean Density kg/m <sup>3</sup> |             | >500 kg/m <sup>3</sup> |
| Surface<br>treatment                                                                                                                                                                                                                            | Oil                                                  | Grading              | Dynamic             | Reaction To Fire                       | EN13501-1   | Dfl-s1                 |
| Design<br>features                                                                                                                                                                                                                              | Bevelled 4-sided, handscraped, brushed, light smoked | Range                | Kährs Original      | Formaldehyde Emission                  | EN717-1     | E1                     |
|                                                                                                                                                                                                                                                 |                                                      | Collection           | Founders Collection | Content PCP                            | CEN/TR14823 | ≤5 x 10-6n             |
| Dimensions                                                                                                                                                                                                                                      | 2420 x 187 x 15 mm                                   | Resandable           | 2-3 times           | Breaking Strength Nmm <sup>2</sup>     | EN1533      | NPD                    |
| Weight per<br>Package                                                                                                                                                                                                                           | 22 kg                                                | Natural/Stained      | Stained             | Thermal Conductivity                   | EN12664     | 0,14 W/mK              |
| Area per<br>Package                                                                                                                                                                                                                             | 2.72 m <sup>2</sup>                                  | Brinell Value        | 3,7                 | Thermal Resistance R-Value             |             | .11 (m2K/W)            |
|                                                                                                                                                                                                                                                 |                                                      | Joint                | Woodloc® 5S         | <b>Biological Durability</b>           | EN350-2     | Class 1                |
| Area Per<br>Board                                                                                                                                                                                                                               | 0.453 m <sup>2</sup>                                 | Roor heating         | Yes                 | CARB2                                  |             | Compliant              |
|                                                                                                                                                                                                                                                 |                                                      | Warranty             | 30 years            |                                        |             |                        |
| DETAIL DESCRIPTION                                                                                                                                                                                                                              |                                                      | Wear-layer material  | Hardwood            |                                        |             |                        |
| All naturally occuring wood colour variations<br>allowed, from light to dark brown. Sapwood<br>may occur. The product includes very large<br>sound and black knots and cracks. Knots and<br>cracks will be present in all sizes and<br>numbers. |                                                      | Wear-layer thickness | 3, 5 mm             |                                        |             |                        |
|                                                                                                                                                                                                                                                 |                                                      | Core material        | Pine/Spruce lamella |                                        |             |                        |
|                                                                                                                                                                                                                                                 |                                                      | Thickness            | 15 mm               |                                        |             |                        |
|                                                                                                                                                                                                                                                 |                                                      | Installation method  | Glue-down, floating |                                        |             |                        |
| numbers.                                                                                                                                                                                                                                        |                                                      | EAN Code             | 7393969036054       |                                        |             |                        |
| COLOUR CHANGE                                                                                                                                                                                                                                   |                                                      | Surface Colour       | Grey FM             |                                        |             |                        |

Stained product - noticable color change over time.

## CERTIFICATES