

# **OAK SUN**

This single-strip oak floor from the Lux Collection features warm, washed undertones, with a lighter and calmer expression than most conventional natural oak floors. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the faintly burnished nuances in the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DESCRIPTION		
Article Number	151N8AEK04KW240	
Surface treatment	Ultra matt lacquer	
Design features	Microbevelled 4-sided, brushed	
Dimensions	2420 x 187 x 15 mm	
Weight per Package	22 kg	
Area per Package	2.72 m²	
Area Per Board	0.453 m <sup>2</sup>	

### DETAIL DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and fillings. Knots and fillings may vary in size and numbers.

## COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

FACTS		
Wood Species	Oak	
Board	1-strip	
Grading	Lively (Country)	
Range	Kährs Original	
Collection	Lux Collection	
Resandable	2-3 times	
Natural/Stained	Natural	
Brinell Value	3, 7	
Joint	Woodloc® 5S	
Roor heating	Yes	
Warranty	30 years	
Wear-layer material	Hardwood	
Wear-layer thickness	3, 5 mm	
Core material	Pine/Spruce/Alder	
Backside material	Spruce	
Thickness	15 mm	
Installation method	Floating, glue-down	
EAN Code	7393969044172	

#### TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m <sup>3</sup>
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

### CERTIFICATES

