



## OAK SUOLOM

The rich brown hues in this smoked, single-strip oak floor from the Domani Collection highlight its rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151XCDEKWHKW190	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Design features	Handscraped, microbevelled 4-sided, light smoked	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1900 x 190 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	17.14 kg	Collection	Domani Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Status in Movex	20	Resandable	2-3 times	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Area per Package	2.17 m <sup>2</sup>	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Area Per Board	0.361 m <sup>2</sup>	Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m <sup>2</sup> K/W)
<b>DETAIL DESCRIPTION</b>		Joint	Woodloc®	Biological Durability	EN350-2	Class 1
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Floor heating	Yes	<b>CARB2</b>		Compliant
<b>COLOUR CHANGE</b>		Warranty	30 years			
Stained product - noticeable color change over time.		Wear-layer material	Hardwood			
<b>CERTIFICATES</b>		Wear-layer thickness	3, 5 mm			
		Core material	Spruce			
		Backside material	Veneer			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969041461			
		Surface Colour	Brown			

