

OAK TERRA

This single-strip oak floor from the Lux Collection features saturated earth tones highlighted by a rich smoke finish, which accentuates the naturally occurring blemishes in the timber. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the darker nuances in the grain for a timeless, rustic expression. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DESCRIPTION	
Article Number	151N8AEKF4KW240
Surface treatment	Ultra matt lacquer
Design features	Microbevelled 4-sided, brushed, smoked
Dimensions	2420 x 187 x 15 mm
Weight per Package	22 kg
Area per Package	2.72 m²
Area Per Board	0.453 m ²

DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers. The smoked design enhances.

COLOUR CHANGE

Smoked product - noticable color change over time

FACTS	
Wood Species	Oak
Board	1-strip
Grading	Lively (Country)
Range	Kährs Original
Collection	Lux Collection
Resandable	2-3 times
Natural/Stained	Natural
Brinell Value	3,7
Joint	Woodloc® 5S
Roor heating	Yes
Hoor heating Warranty	Yes 30 years
Warranty	30 years
Warranty Wear-layer material	30 years Hardwood
Warranty Wear-layer material Wear-layer thickness	30 years Hardwood 3, 5 mm
Warranty Wear-layer material Wear-layer thickness Core material	30 years Hardwood 3, 5 mm Pine/Spruce/Alder
Warranty Wear-layer material Wear-layer thickness Core material Backside material	30 years Hardwood 3, 5 mm Pine/Spruce/Alder Spruce
Warranty Wear-layer material Wear-layer thickness Core material Backside material Thickness	30 years Hardwood 3, 5 mm Pine/Spruce/Alder Spruce 15 mm

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength Wmm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATES

