



## OAK ULF

The dark brown tones in this single-strip oak floor from the Founders Collection are enriched by a beautifully smoked finish, resulting in a warm, dark greystain punctuated by charcoal knots and cracks. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N7BEKFBKW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Design features	Bevelled 4-sided, handscraped, brushed	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Founders Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m <sup>2</sup>	Resandable	2-3 times	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Area Per Board	0.453 m <sup>2</sup>	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m <sup>2</sup> K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Glue-down, floating			
		EAN Code	7393969036030			
		Surface Colour	Dark Grey FG			
<b>DETAIL DESCRIPTION</b>						
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.						
<b>COLOUR CHANGE</b>						
Stained product - noticable color change over time.						
<b>CERTIFICATES</b>						

