

# **OAK VEDBO**

The warm golden stain on this single-strip oak floor from the Småland Collection enhances the late autumn harvest tones in the wood, resulting in a lively expression and naturally balanced contrast. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the worn appearance of the floor.

| PRODUCT DESCRIPTION   |  |  |
|-----------------------|--|--|
| Article<br>Number     | 151NCSEK01KW240                        |  |
| Surface<br>treatment  | Oil                                    |  |
| Design<br>features    | Bevelled 4-sided, brushed, handscraped |  |
| Dimensions            | 2420 x 187 x 15 mm                     |  |
| Weight per<br>Package | 22 kg                                  |  |
| Area per<br>Package   | 2.72 m <sup>2</sup>                    |  |
| Area Per<br>Board     | 0.453 m <sup>2</sup>                   |  |

## DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

| FACTS                         |                           |  |
|-------------------------------|---------------------------|--|
| Wood Species                  | Oak                       |  |
| Board                         | 1-strip                   |  |
| Grading                       | Dynamic                   |  |
| Range                         | Kährs Supreme             |  |
| Collection                    | Småland Collection        |  |
| Resandable                    | 2-4 times                 |  |
| Natural/Stained               | Natural                   |  |
| Brinell Value                 | 3,7                       |  |
| Joint                         | Woodloc® 5S               |  |
| Roor heating                  | Yes                       |  |
| Warranty                      | 30 years                  |  |
| Wear-layer material           | Hardwood                  |  |
| Wear-layer thickness          | 3, 5 mm                   |  |
| Core material                 | Pine/Spruce lamella       |  |
| Backside material             | Veneer                    |  |
|                               |                           |  |
| Thickness                     | 15 mm                     |  |
| Thickness Installation method | 15 mm Floating, glue-down |  |
|                               |                           |  |

#### TECHNICAL PROPERTIES

| EN13183     | 7%±2%  |
|-------------|--|
|             | >500 kg/m <sup>3</sup>                                   |
| EN13501-1   | Dfl-s1   |
| EN717-1     | E1   |
| CEN/TR14823 | ≤ 5 x 10-6n  |
| EN1533      | NPD  |
| EN12664     | 0,14 W/mK  |
|             | .11 (m2K/W)  |
| EN350-2     | Class 1  |
|             | Compliant  |
|             | EN13501-1<br>EN717-1<br>CEN/TR14823<br>EN1533<br>EN12664 |

#### CERTIFICATES

