



## OAK WILDS

The lightly smoked finish on this single-strip oak floor from the Habitat Collection enhances its broad colour variation, which ranges from espresso brown to wheat blonde. The naturally occurring knots and cracks highlight its rustic expression and add depth to the floor. Four-sided bevelling at the edges ensures a classic full plank look and feel. Each board is carefully brushed to bring out the character of the grain and the natural texture of the wood.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES			
<b>Article Number</b>	37107AEKFCKW180	<b>Wood Species</b>	Oak	<b>Moisture content</b>	EN13183	7%±2%	
<b>Surface treatment</b>	Oil	<b>Board</b>	1-strip	<b>Minimum Mean Density kg/m³</b>		>800 kg/m³	
<b>Design features</b>	Microbevelled 4-sided, brushed, light smoked	<b>Grading</b>	Dynamic	<b>Reaction To Fire</b>	EN13501-1	Cfl-s1	
<b>Dimensions</b>	1810 x 150 x 7 mm	<b>Range</b>	Kährs Linnea	<b>Formaldehyde Emission</b>	EN717-1	E1	
<b>Weight per Package</b>	20 kg	<b>Collection</b>	Habitat Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n	
<b>Status in Movex</b>	20	<b>Resandable</b>	Not resandable	<b>Breaking Strength N/mm²</b>	EN1533	NPD	
<b>Area per Package</b>	3.26 m²	<b>Natural/Stained</b>	Natural	<b>Thermal Conductivity</b>	EN12664	0,22 W/mK	
<b>Area Per Board</b>	0.272 m²	<b>Brinell Value</b>	5 - 6	<b>Thermal Resistance R-Value</b>		.031 (m2K/W)	
<b>DETAIL DESCRIPTION</b>	All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		<b>Joint</b>	Woodloc®	<b>Biological Durability</b>	EN350-2	Class 1
<b>COLOUR CHANGE</b>	Some muting of colour variation to medium, straw brown.		<b>Floor heating</b>	Yes	<b>CARB2</b>		Compliant
		<b>Warranty</b>	12 years				
		<b>Wear-layer material</b>	Hardwood				
		<b>Wear-layer thickness</b>	0,6 mm				
		<b>Core material</b>	HDF				
		<b>Thickness</b>	7 mm				
		<b>Installation method</b>	Floating, glue-down				
		<b>EAN Code</b>	7393969107082				
		<b>CERTIFICATES</b>					

