

OAK YDRE

The smoked stone stain on this single-strip oak floor from the Småland Collection allows the cooler nuances in the base to come through, resulting in a smooth and harmoniously balanced expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151NCSEK04KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
		Board	1-strip	Minimun Mean Density kg/m³		>500 kg/m³
Surface treatment	Oil	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Bevelled 4-sided, brushed, light smoked, handscraped	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1
		Collection	Småland Collection	Content PCP	CEN/TR14823	≤5 x 10-6n
Dimensions	2420 x 187 x 15 mm	Resandable	2-4 times	Breaking Strength Wmm²	EN1533	NPD
Weight per Package	22 kg	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Area per Package	2.72 m ²	Brinell Value	3,7	Thermal Resistance R-Value		.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Area Per Board	0.453 m ²	Roor heating	Yes	CARB2		Compliant
		Warranty	30 years			
DETAIL DESCRIPTION		Wear-layer material	Hardwood			
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Backside material	Veneer			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
COLOUR CHANGE		EAN Code	7393969038997			

Mineral Grey

Surface Colour

CERTIFICATES

Stained product - noticable color change over

