



PARK OAK

The natural tones in this single-strip oak floor from the Unity Collection range from dark chocolate to bleached straw, and are scattered with knots for an earthy, rustic expression. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	101P6AEK09KW120	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Matt lacquer	Board	1-strip	Minimum Mean Density kg/m ³		>800 kg/m ³
Design features	Bevelled 4-sided, brushed	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1200 x 125 x 10 mm	Range	Kährs Spirit	Formaldehyde Emission	EN717-1	E1
Weight per Package	14 kg	Collection	Unity Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	1.50 m ²	Resandable	1 time	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.150 m ²	Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
COLOUR CHANGE		Joint	Woodloc®	Thermal Resistance R-Value		.07 (m ² K/W)
Some muting of colour variation to medium, straw brown.		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Warranty	20 years	CARB2		Compliant
		Wear-layer material	Hardwood			
		Wear-layer thickness	1,9 mm			
		Core material	HDF			
		Backside material	Veneer			
		Thickness	10 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969030595			

CERTIFICATES

