

POWDER OAK

The blanched oak boards of this single-strip, stained floor from the Unity Collection range in colour from creamy white to heather grey. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	101P3AEK9VKW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Matt lacquer	Board	1-strip	Minimun Mean Density kg/m³		>800 kg/m³
		Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Microbevelled 4-sided, brushed	Range	Kährs Spirit	Formaldehyde Emission	EN717-1	E1
Dimensions	1830 x 125 x 10 mm	Collection	Unity Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	16, 75 kg	Resandable	1 time	Breaking Strength Wmm ²	EN1533	NPD
		Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Area per Package	1.83 m²	Brinell Value	3, 7	Thermal Resistance R-Value		.07 (m2K/W)
Area Per Board	0.229 m²	Joint	Woodloc®	Biological Durability	EN350-2	Class 1
		Roor heating	Yes	CARB2		Compliant
DETAIL DESCRIPTION		Warranty	20 years			
Naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and fillings. Knots and fillings may vary in size and numbers. COLOUR CHANGE		Wear-layer material	Hardwood			
		Wear-layer thickness	1, 9 mm			
		Core material	HDF			
		Thickness	10 mm			
		Installation method	Floating, glue-down			
Stained product - noticeable color change over time.		EAN Code	7393969045025			
		Surface Colour	White			

CERTIFICATES

