

WALNUT GROOVE

Arich palette of robust browns is enhanced with natural oiling and extra-deep brushing to bring out the character of the grain and highlight the natural texture of the wood, in this single-strip walnut floor from the Rugged Collection. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION			
Article Number	101P8HVAF0KW180		
Surface treatment	Oil		
Design features	Brushed, handscraped, microbevelled 4-sided		
Dimensions	1830 x 125 x 10 mm		
Weight per Package	16, 75 kg		
Area per Package	1.83 m ²		
Area Per Board	0.228 m ²		

DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Changes to golden brown.

CERTIFICATES

Wood Species	Walnut	
Board	1-strip	
Grading	Dynamic	
Range	Kährs Spirit	
Collection	Rugged Collection	
Resandable	1 time	
Natural/Stained	Natural	
Joint	Woodloc®	
Roor heating	Yes	
Warranty	20 years	
Wear-layer material	Hardwood	
Wear-layer thickness	1, 9 mm	
Core material	HDF	
Thickness	10 mm	
Installation method	Floating, glue-down	
EAN Code	7393969043847	

FACTS

TECHNICAL PROPERTIES

Moisture content EN13183 7%±2% Minimun Mean Density kg/m³ >800 kg/m³ Reaction To Fire EN13501-1 Dfl-s1 Formaldehyde Emission EN717-1 E1 Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength N/mm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .07 (m2K/W) Biological Durability EN350-2 Class 1 CARB2 Compliant			
Reaction To Fire EN13501-1 Dfl-s1 Formaldehyde Emission EN717-1 E1 Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength Wmm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .07 (m2K/W) Biological Durability EN350-2 Class 1	Moisture content	EN13183	7%±2%
Formaldehyde Emission EN717-1 E1 Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength N/mm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .07 (m2K/W) Biological Durability EN350-2 Class 1	Minimun Mean Density kg/m³		>800 kg/m³
Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength Wmm² EN1533 NPD Thermal Conductivity EN12664 0,14 WmK Thermal Resistance R-Value .07 (m2K/W) Biological Durability EN350-2 Class 1	Reaction To Fire	EN13501-1	Dfl-s1
Breaking Strength N/mm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .07 (m2K/W) Biological Durability EN350-2 Class 1	Formaldehyde Emission	EN717-1	E1
Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .07 (m2K/W) Biological Durability EN350-2 Class 1	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Thermal Resistance R-Value .07 (m2K/W) Biological Durability EN350-2 Class 1	Breaking Strength N/mm²	EN1533	NPD
Biological Durability EN350-2 Class 1	Thermal Conductivity	EN12664	0,14 W/mK
	Thermal Resistance R-Value		.07 (m2K/W)
CARB2 Compliant	Biological Durability	EN350-2	Class 1
	CARB2		Compliant

